

MIA PEANUT VINE CONDITIONER

6000



ONE MODEL, MULTIPLE USE OPTIONS

- Use in 1, 2 or 3 windrows as required
- Conditions crop for efficient harvesting
- Coupling system in operation





With the tractor in full operation and with simple activation by hydraulic remote you can lift one or both conveyors of the conditioner to finish hard to reach areas (level curves, dead lines and corners). Its main function is to facilitate harvesting by removing clods and lifting the peanut branches from the humid soil.

- Convenience
- Flexibility
- Gains harvest time
- Operational quality

ESQUEMA DE OPÇÕES DE USO



For jobs requiring 1 line



For jobs requiring 2 lines



For jobs requiring 3 lines

TECHNICAL SPECIFICATIONS

Necessary engine power	90 hp
Coupling	3rd point (category II)
Activation	Hidraulic
Work Speed	2.5-3 MPH

Dimensions and Weight

Height	51 in (1,300 mm)
Length	49 in (1,250 mm)
Overall equipment width	19.67 feet (6,000 mm)
Running	165/70 R13
Weight	1,655 lbs (750 kg)

Product improvement is one of COLOMBO priorities. COLOMBO reserves the right to introduce changes in product components and accessories without previous notice.

Marketing - 171.719-1 - Rev. 3 - 09/24